



Scheda n. 057

B15 - RINA MED 

WINDOW

General Information	
description	windows and side scuttles
type	large window
manufacturer	Precetti SpA
Application	
fire properties	B15 Class fire resistant
certificates, approvals	RINA MED Module B Nr. MED525707CS/002
drawing number	B0050005277
Size	
max horizontal clear opening (LNO)	1050 mm
max vertical clear opening (LNV)	1984 mm
horizontal cut in bulkhead (TPO)	LNO + 100 mm + 10 mm
vertical cut in bulkhead (TPV)	LNV + 100 mm + 10 mm
Frame	
section shape	see dwg
section size	see dwg
thickness of steel	1,5 mm
materials	steel or stainless steel (ss)
finishing	raw, paint, brushed or polished (ss)
counter frame thickness	1,5 mm
Leaf	
glass	PYROBEL
thickness minimum of glass	16 +/- 1 mm
thickness of window	60 mm
Accessories	
decoration	custom request
Mechanical and physical properties	
noise reduction	n.a.

Product data sheet

B15_window_rev00

Sede operativa:
Via Dante, 2/7
16121 Genova, Italia

Sede legale:
Via Fieschi, 20/9
16121 Genova, Italia

info@blubud.it
t +39 010 89 95 535/536
f +39 010 89 95 537

www.blubud.it
c.f. e p.iva 01766240996
Reg. impr. Genova REA 43442